

AD-A107 913

CALIFORNIA UNIV BERKELEY OPERATIONS RESEARCH CENTER

F/6 12/1

A SIMPLE HEURISTIC APPROACH TO SIMPLEX EFFICIENCY.(U)

AUG 81 S M ROSS

AFOSR-81-0122

UNCLASSIFIED

ORC-81-21

NL

1 of 1
AD
A-07-01



END
DATE
FILMED
1-82
DTIC


ORC 81-21
AUGUST 1981

12
LEVEL II

A SIMPLE HEURISTIC APPROACH TO SIMPLEX EFFICIENCY

by
SHELDON M. ROSS

AD A107913



OPERATIONS
RESEARCH
CENTER

WIC FILE COPY

DTIC
ELECTE
DEC 1 1981
S D

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

UNIVERSITY OF CALIFORNIA • BERKELEY

81 12 01 022

A SIMPLE HEURISTIC APPROACH TO SIMPLEX EFFICIENCY

by

Sheldon M. Ross
Department of Industrial Engineering
and Operations Research
University of California, Berkeley

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

DTIC
ELECTE
S DEC 1 1981 D
D

AUGUST 1981

ORC 81-21

This research was supported by the Air Force Office of Scientific Research (AFSC), USAF, under Grant AFOSR-81-0122 with the University of California. Reproduction in whole or in part is permitted for any purpose of the United States Government.

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

12 12

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ORC-81-21	2. GOVT ACCESSION NO. AD A307913	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A SIMPLE HEURISTIC APPROACH TO SIMPLEX EFFICIENCY		5. TYPE OF REPORT & PERIOD COVERED Research Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Sheldon M. Ross		8. CONTRACT OR GRANT NUMBER(s) AFOSR-81-0122
9. PERFORMING ORGANIZATION NAME AND ADDRESS Operations Research Center University of California Berkeley, California 94720		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 2304/A5
11. CONTROLLING OFFICE NAME AND ADDRESS United States Air Force Air Force Office of Scientific Research Bolling Air Force Base, D.C. 20332		12. REPORT DATE August 1981
		13. NUMBER OF PAGES 11
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Linear Programming Simplex Algorithm Probabilistic Analysis Poisson		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) (SEE ABSTRACT)		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

ABSTRACT

Consider the standard linear program:

Minimize $\underline{c} \underline{x}$

subject to: $A \underline{x} = \underline{b}$

$\underline{x} \geq 0$

where A is an $m \times n$ matrix. The simplex algorithm solves this linear program by moving from extreme point of the feasibility region to a better (in terms of the objective function $\underline{c} \underline{x}$) extreme point (via the pivot operation) until the optimal is reached. In order to obtain a feel for the number of necessary iterations, we consider a simple probabilistic (Markov chain) model as to how the algorithm moves along the extreme points. At first we suppose that if at any time the algorithm is at the j th best extreme point then after the next pivot the resulting extreme point is equally likely to be any of the $j - 1$ best. Under this assumption, we show that the time to get from the N th best to the best extreme point has approximately, for large N , a Poisson distribution with mean equal to the logarithm (base e) of N . We also consider a more general probabilistic model in which we drop the uniformity assumption and suppose that when at the j th best the next one is chosen probabilistically according to weights w_i , $i = 1, \dots, j - 1$.

A SIMPLE HEURISTIC APPROACH TO SIMPLEX EFFICIENCY

by

Sheldon M. Ross

1. INTRODUCTION

Consider the standard linear program:

Minimize $\underline{c} \underline{x}$

subject to: $A \underline{x} = \underline{b}$

$\underline{x} \geq 0$

where A is an $m \times n$ matrix. The simplex algorithm solves this linear program by moving from extreme point of the feasibility region to a better (in terms of the objective function $\underline{c} \underline{x}$) extreme point (via the pivot operation) until the optimal is reached. As there are roughly $N \equiv \binom{n}{m}$ such extreme points it would seem that this method might take many iterations but, surprisingly to some, this does not appear to be the case in practice.

In order to obtain a feel for whether or not the above is surprising, we consider a simple probabilistic (Markov chain) model as to how the algorithm moves along the extreme points. At first we suppose that if at any time the algorithm is at the j th best extreme point then after the next pivot the resulting extreme point is equally likely to be any of the $j - 1$ best. Under this assumption, we show that the time to get from the N th best to the best extreme point has approximately, for large N , a Poisson distribution with mean equal to the logarithm (base e) of N . We also consider a more general probabilistic model

in which we drop the uniformity assumption and suppose that when at the j th best the next one is chosen probabilistically according to weights w_i , $i = 1, \dots, j - 1$.

2. THE UNIFORM MARKOV CHAIN

Consider a Markov chain for which $P_{11} = 1$ and

$$P_{ij} = \frac{1}{i-1}, \quad j = 1, \dots, i-1, \quad i > 1$$

and let T_N denote the number of transitions to get from state N to state 1. Then T_N can be expressed as

$$T_N = \sum_{j=1}^{N-1} I_j$$

where

$$I_j = \begin{cases} 1 & \text{if the process ever enters } j \\ 0 & \text{otherwise.} \end{cases}$$

Proposition 1:

I_1, \dots, I_{N-1} are independent and

$$P\{I_j = 1\} = 1/j, \quad 1 \leq j \leq N-1.$$

Proof:

Given I_{j+1}, \dots, I_N let $n = \min \{i : i > j, I_i = 1\}$. Then

$$P\{I_j = 1 \mid I_{j+1}, \dots, I_N\} = \frac{1/(n-1)}{j/(n-1)} = 1/j. \blacksquare$$

Corollary 2:

$$(i) \quad E[T_N] = \sum_{j=1}^{N-1} 1/j$$

$$(ii) \quad \text{Var}(T_N) = \sum_{j=1}^{N-1} \frac{1}{j} \left(1 - \frac{1}{j}\right)$$

(iii) For N large, T_N has approximately a Poisson distribution with mean $\log N$.

Proof:

Parts (i) and (ii) follow from Proposition 1 and the representation

$$T_N = \sum_{j=1}^{N-1} I_j. \quad \text{Part (iii) follows from the Poisson limit theorem since}$$

$$\int_1^N \frac{dx}{x} < \sum_{j=1}^{N-1} 1/j < 1 + \int_1^{N-1} \frac{dx}{x}$$

or

$$\log N < \sum_{j=1}^{N-1} 1/j < 1 + \log(N-1)$$

and so

$$\log N \approx \sum_{j=1}^{N-1} 1/j. \blacksquare$$

3. APPLICATION TO SIMPLEX

Assuming that n , m and $n - m$ are all large, we have by Stirling's approximation that

$$N = \binom{n}{m} \sim \frac{n^{n+1/2}}{(n-m)^{n-m+1/2} m^{m+1/2} \sqrt{2\pi}}$$

and so letting $c = n/m$

$$\begin{aligned} \log N &\sim (mc + 1/2) \log (mc) - (m(c-1) + 1/2) \log (m(c-1)) \\ &\quad - (m + 1/2) \log m - 1/2 \log (2\pi) \end{aligned}$$

or

$$\log N \sim m \left[c \log \frac{c}{c-1} + \log (c-1) \right].$$

Now, as $\lim_{x \rightarrow \infty} x \log (x/x-1) = 1$, it follows that when c is large

$$\log N \sim m[1 + \log (c-1)].$$

Thus for instance if $n = 8000$, $m = 1000$, then the number of necessary transitions is approximately Poisson distributed with mean $1000(1 + \log 7) \approx 3000$. As the variance is equal to the mean, we see by the normal approximation to the Poisson that the number of necessary transitions would be roughly between

$$3000 \pm 2\sqrt{3000} \text{ or, roughly, } 3000 \pm 110$$

95 percent of the time.

4. A WEIGHTED MARKOV CHAIN MODEL

Suppose now that $P_{11} = 1$ and

$$P_{ij} = \frac{w_j}{w_1 + \dots + w_{i-1}} \quad j \leq i - 1.$$

With this model we are thus able to give more weight to those states closest to the one presently at by letting w_j increase in j .

Analogously with Proposition 1, we have

Proposition 2:

If

$$I_j = \begin{cases} 1 & \text{if } j \text{ is ever visited} \\ 0 & \text{otherwise.} \end{cases}$$

Then I_1, \dots, I_{N-1} are independent and

$$P\{I_j = 1\} = \frac{w_j}{\sum_{i=1}^j w_i}, \quad 1 \leq j \leq N-1.$$

In addition, if $T_N = \sum_{j=1}^{N-1} I_j$. Then

$$E[T_N] = \sum_{j=1}^{N-1} \left(w_j / \sum_{i=1}^j w_i \right)$$

$$\text{Var}(T_N) = \sum_{j=1}^{N-1} \frac{w_j}{\sum_{i=1}^j w_i} \left(1 - \frac{w_j}{\sum_{i=1}^j w_i} \right).$$

If for instance we use polynomial weights-- $w_j = j^\alpha$, $0 \leq \alpha < \infty$, then

$$\begin{aligned} \sum_{i=1}^j w_i &= \sum_{i=1}^j i^\alpha \\ &\approx \int_1^j x^\alpha dx \\ &= \frac{j^{\alpha+1} - 1}{\alpha + 1} \end{aligned}$$

and so

$$\frac{w_j}{\sum_{i=1}^j w_i} \approx \frac{(\alpha + 1)j^\alpha}{j^{\alpha+1} - 1} \approx \frac{\alpha + 1}{j}.$$

Hence

$$E[T_N] \approx \int_1^{N-1} \frac{\alpha + 1}{x} dx = (\alpha + 1) \log (N - 1)$$

and thus in this case T_N has, for large N , approximately a Poisson distribution with mean $(\alpha + 1) \log N$. Thus when $N = \binom{n}{m}$, the number of transitions (i.e., simplex pivot iterations) is approximately Poisson with mean

$$(\alpha + 1)m \left[c \log \left(\frac{c}{c-1} \right) + \log (c - 1) \right], \quad c = n/m$$

which when c is large is approximately

$$(\alpha + 1)m[1 + \log (c - 1)].$$

REFERENCES

- Dantzig, G. B., "Expected Number of Steps of the Simplex Method for a Linear Program with a Convexity Constraint," Systems Optimization Laboratory Technical Report SOL 80-3, Stanford University, March 1980.
- Liebling, T. M., "On the Number of Iterations of the Simplex Method," Methods of Operations Research, XVII, V, Oberwolfach-Tagung uber Operations Research, 13-19, August 1977, 248-264.
- Orden, A., "A Step Towards Probabilistic Analysis of Simplex Convergence," Mathematical Programming, 19, 1980, 3-13.